



1969 Rutgers University Blvd Suite 201
Lakewood NJ 08701
732-719-9798
www.maxspacestorage.com

Storage Unit Specifications

Partition Wall: Corrugated 26-gauge panel can be used as a divider partition inside each unit or as a hallway panel to keep costs at a minimum.

Corridor Wall: Flush 20-gauge hallway panel manufactured in 12" wide, interlocking panels, and engineered so that the screws are not exposed. Wall panels provide maximum security and are easy to keep clean.

Swing Door: Doors are manufactured with an extruded aluminum frame and the cross brace on the back of the door add strength to the swing door. Door frame and header are manufactured from 20-gauge steel to the height required in the hallway.

Mid Span Brace: 20-gauge channel provides added strength and integrity to walls.

Corner Guards and Kick Plates: Corner guards protect exposed corners in the hallway and are available up to 10 ft. Available in 20-gauge galvanized steel and aluminum diamond plate.

Kick plates are installed at the bottom of the hallway to prevent damage caused by tenants moving into the storage unit. Kick plates are available in 20-gauge galvanized steel and aluminum diamond plate.

Wire Mesh: A low cost, yet highly effective method of securing contents while allowing ventilation and lighting inside each unit. Available in 2"x2" mesh- 16-gauge.